

Safety data sheet

according to 1907/2006/EC, Article 31

Fotospeed
for every print

Printing date 29.07.2021

version no: 10

Revision: 29.07.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Fotospeed (DV-10) B&W PAPER DEVELOPER**

Article number: 100138

Number

None of the ingredients is listed.

UFI: 1C80-80S3-P00Y-0PN8

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Black and white developer for photographic use

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Jay House LTD

Lower Beaversbrook, Industrial Estate, Redman Road, Calne, SN11 9PL

Tel.: +44 (0) 1249714555; www.Fotospeed.com;

E-mail: info@fotospeed.com

Further information obtainable from: Department product safety. E-Mail: info@fotospeed.com .

1.4 Emergency telephone number:

Jay House Ltd Tel.:+44(0) 1249 714555 (open: 8am till 5pm)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Muta. 2 H341 Suspected of causing genetic defects.

Carc. 2 H351 Suspected of causing cancer.

Aquatic Acute 1 H400 Very toxic to aquatic life.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS05



GHS07



GHS08



GHS09

Signal word Danger

Hazard-determining components of labelling:

hydroquinone

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

(Contd. on page 2)

Trade name: Fotospeed (DV-10) B&W PAPER DEVELOPER

(Contd. of page 1)

P264	Wash thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below and with nonhazardous additions.

Dangerous components:

CAS: 123-31-9	hydroquinone	1-5%
EINECS: 204-617-8	☠ Muta. 2, H341; Carc. 2, H351; ☠ Eye Dam. 1, H318; ☠ Aquatic	
Index number: 604-005-00-4	Acute 1, H400 (M=10); ☠ Acute Tox. 4, H302; Skin Sens. 1, H317	
Reg.nr.: 01-2119524016-51		
CAS: 584-08-7	potassium carbonate	1-5%
EINECS: 209-529-3	☠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
Reg.nr.: 01-2119532646-36		
CAS: 1330-43-4	disodium tetraborate, anhydrous	1-5%
EINECS: 215-540-4	☠ Repr. 1B, H360FD	
Index number: 005-011-00-4		
CAS: 140-01-2	Diethylenetriaminepentaacetic acid, pentasodium salt (DTPA-Na5)	1-5%
EINECS: 205-391-3	☠ STOT RE 2, H373; ☠ Acute Tox. 4, H332	
Index number: 607-736-00-7		
Reg.nr.: 01-2119474445-33		
CAS: 1310-73-2	sodium hydroxide (caustic soda)	<1%
EINECS: 215-185-5	☠ Met. Corr.1, H290; Skin Corr. 1A, H314	
Index number: 011-002-00-6		
Reg.nr.: 01-2119457892-27		

SVHC

1330-43-4 disodium tetraborate, anhydrous

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing/shoes soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Trade name: Fotospeed (DV-10) B&W PAPER DEVELOPER

(Contd. of page 2)

- . **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- . **After swallowing:**
Do not induce vomiting; call for medical help immediately.
Drink plenty of water and provide fresh air. Call for a doctor immediately.
- . **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- . **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- . **5.1 Extinguishing media**
- . **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- . **5.2 Special hazards arising from the substance or mixture**
Nitrogen oxides (NOx)
Carbon monoxide (CO)
Sulphur dioxide (SO₂)
Under certain fire conditions, traces of other toxic gases cannot be excluded.
- . **5.3 Advice for firefighters**
- . **Protective equipment:** Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- . **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective clothing.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- . **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- . **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- . **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- . **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- . **Information about fire - and explosion protection:** No special measures required.
- . **7.2 Conditions for safe storage, including any incompatibilities**
- . **Storage:**
- . **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- . **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidising agents.
- . **Further information about storage conditions:**
Recommended storage temperature: 15-25°C

(Contd. on page 4)

Trade name: Fotospeed (DV-10) B&W PAPER DEVELOPER

(Contd. of page 3)

- Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.
- Store under lock and key and out of the reach of children.
- Recommended storage temperature: 5-30°C
- Protect from exposure to the light.
- . **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

. **8.1 Control parameters**

. **Additional information about design of technical facilities:** No further data; see item 7.

. **Ingredients with limit values that require monitoring at the workplace:**

123-31-9 hydroquinone (1-5%)

- WEL (Great Britain) Long-term value: 0.5 mg/m³
- PEL (USA) Long-term value: 2 mg/m³
- REL (USA) Ceiling limit: 2* mg/m³
*15-min
- TLV (USA) Long-term value: 1 mg/m³
DSEN

1330-43-4 disodium tetraborate, anhydrous (1-5%)

- WEL (Great Britain) Long-term value: 1 mg/m³
- REL (USA) Long-term value: 1 mg/m³
anhydrous
- TLV (USA) Short-term value: 6* mg/m³
Long-term value: 2* mg/m³
*as inhalable fraction

1310-73-2 sodium hydroxide (caustic soda) (<1%)

- WEL (Great Britain) Short-term value: 2 mg/m³
- PEL (USA) Long-term value: 2 mg/m³
- REL (USA) Ceiling limit: 2 mg/m³
- TLV (USA) Ceiling limit: 2 mg/m³

. **DNELs**

123-31-9 hydroquinone

- | | | |
|------------|----------------------------------|------------------------------|
| Dermal | Long-term - systemic - effects | 128 mg/kg bw/day (wkd) |
| | Long-term - systemic effects | 64 mg/kg bw/day (wkd) |
| Inhalative | Long-term exposure-local effects | 7 mg/m ³ (wkd) |
| | Long-term - local - effects | 1 mg/m ³ (wkd) |
| | Long-term - systemic effects | 1.74 mg/m ³ (wkd) |
| | Long-term - local effects | 0.5 mg/m ³ (wkd) |

. **PNECs**

123-31-9 hydroquinone

- | | |
|--|------------------------------------|
| Aquatic compartment - freshwater | 0.000114 mg/l (Water) |
| Aquatic compartment - marine water | 0.000114 mg/l (Water) |
| Aquatic compartment -water,intermittent releases | 0.00134 mg/l (Water) |
| Aquatic compartment -sediment in freshwater | 0.00098 mg/kg sed dw (Water) |
| Aquatic compartment -sediment in marine water | 0.000097 mg/kg sed dw (Water) |
| Terrestrial compartment -soil | 0.000129 mg/kg dw (Soil) |
| Sewage treatment plant (Abwasserreinigungsanlagen) | 0.71 mg/l (Sewage Treatment Plant) |

. **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 5)

Trade name: Fotospeed (DV-10) B&W PAPER DEVELOPER

(Contd. of page 4)

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Ensure adequate ventilation

Protection of hands:



Protective gloves

Impervious gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Butyl rubber, BR

Nitrile rubber, NBR

Neoprene gloves

Penetration time of glove material

Glove material	breakthrough-time	layer thickness
Butyl rubber:	≥480 min	≥0,4mm
Nitrile rubber:	≥480 min	≥0,38mm
Neoprene:	≥240 min	≥0,65mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Fluid

Colour: Colourless

Odour: Recognisable

Odour threshold: Not determined.

pH-value at 20 °C: ~11

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.07.2021

version no: 10

Revision: 29.07.2021

Trade name: Fotospeed (DV-10) B&W PAPER DEVELOPER

(Contd. of page 5)

. Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	>100 °C
. Flash point:	Not applicable.
. Flammability (solid, gas):	Not applicable.
. Decomposition temperature:	Not determined.
. Auto-ignition temperature:	Product is not selfigniting.
. Explosive properties:	Product does not present an explosion hazard.
. Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
. Vapour pressure:	Not determined.
. Density at 20 °C:	1.29 g/cm ³
. Relative density	Not determined.
. Vapour density	Not determined.
. Evaporation rate	Not determined.
. Solubility in / Miscibility with water:	Fully miscible.
. Partition coefficient: n-octanol/water:	Not determined.
. Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
. Solvent content:	
Water:	50-90 %
VOC (EC)	0.00 %
 Solids content:	0.0 %
. 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- . 10.1 Reactivity No further relevant information available.
- . 10.2 Chemical stability
- . Thermal decomposition / conditions to be avoided: Stable at environment temperature.
- . 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- . 10.4 Conditions to avoid No further relevant information available.
- . 10.5 Incompatible materials: Under certain fire conditions, traces of other toxic gases cannot be excluded.
- . 10.6 Hazardous decomposition products:
 - Nitrogen oxides (NO_x)
 - Irritant gases/vapours
 - Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- . 11.1 Information on toxicological effects
- . Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

-EN-

Trade name: Fotospeed (DV-10) B&W PAPER DEVELOPER

(Contd. of page 6)

LD/LC50 values relevant for classification:

123-31-9 hydroquinone

Oral LD50 302 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rabbit)

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Additional toxicological information:

Acute effects (acute toxicity, irritation and corrosivity)

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity

Suspected of causing genetic defects.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

123-31-9 hydroquinone

EC50 48 mg/l (daphnia magna (Water flea))

LC50 96 mg/l (fish: Pimephales promelas)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Very toxic for fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Danger to drinking water if even extremely small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

EN

(Contd. on page 8)

Trade name: Fotospeed (DV-10) B&W PAPER DEVELOPER

(Contd. of page 7)

SECTION 13: Disposal considerations

. 13.1 Waste treatment methods

. Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

. European waste catalogue

09 00 00 WASTES FROM THE PHOTOGRAPHIC INDUSTRY

09 01 00 wastes from the photographic industry

09 01 01* water-based developer and activator solutions

. Uncleaned packaging:

. Recommendation: Disposal must be made according to official regulations.

. Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

. 14.1 UN-Number

. ADR, IMDG, IATA

UN3267

. 14.2 UN proper shipping name

. ADR

3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
(SODIUM HYDROXIDE, hydroquinone),
ENVIRONMENTALLY HAZARDOUS

. IMDG

CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
(SODIUM HYDROXIDE, hydroquinone), MARINE
POLLUTANT

. IATA

CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
(SODIUM HYDROXIDE)

. 14.3 Transport hazard class(es)

. ADR

. Class

8 (C7) Corrosive substances.

. Label

8

. IMDG, IATA

. Class

8 Corrosive substances.

. Label

8

. 14.4 Packing group

. ADR, IMDG, IATA

III

. 14.5 Environmental hazards:

Product contains environmentally hazardous substances:
hydroquinone

. Marine pollutant:

Yes

Symbol (fish and tree)

. Special marking (ADR):

Symbol (fish and tree)

. 14.6 Special precautions for user

Warning: Corrosive substances.

. Hazard identification number (Kemler code):

80

. EMS Number:

F-A,S-B

. Segregation groups

Alkalis

. Stowage Category

A

. Stowage Code

SW2 Clear of living quarters.

. Segregation Code

SG35 Stow "separated from" SGG1-acids

. 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

(Contd. on page 9)

Trade name: Fotospeed (DV-10) B&W PAPER DEVELOPER

(Contd. of page 8)

. Transport/Additional information:

. ADR

- | | |
|----------------------------|--|
| . Limited quantities (LQ) | 5L |
| . Excepted quantities (EQ) | Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml |
| . Transport category | 3 |
| . Tunnel restriction code | E |

. IMDG

- | | |
|----------------------------|--|
| . Limited quantities (LQ) | 5L |
| . Excepted quantities (EQ) | Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml |

. UN "Model Regulation":

UN 3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (SODIUM HYDROXIDE, HYDROQUINONE), 8, III, ENVIRONMENTALLY HAZARDOUS

. 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

. Labelling according to Regulation (EC) No 1272/2008 GHS label elements

. Directive 2012/18/EU

. Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

. Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

. REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

. National regulations:

. Other regulations, limitations and prohibitive regulations

. Substances of very high concern (SVHC) according to REACH, Article 57

1330-43-4 disodium tetraborate, anhydrous

. 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

. Relevant phrases

- H290 May be corrosive to metals.
 H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H341 Suspected of causing genetic defects.
 H351 Suspected of causing cancer.
 H360FD May damage fertility. May damage the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.

. **Contact:** E: info@fotospeed.com .

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.07.2021

version no: 10

Revision: 29.07.2021

Trade name: Fotospeed (DV-10) B&W PAPER DEVELOPER

(Contd. of page 9)

IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Met. Corr.1: Corrosive to metals – Category 1
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Corr. 1A: Skin corrosion/irritation – Category 1A
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Muta. 2: Germ cell mutagenicity – Category 2
 Carc. 2: Carcinogenicity – Category 2
 Repr. 1B: Reproductive toxicity – Category 1B
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 . * **Data compared to the previous version altered.**

-EN-