

TECHNICAL DATA SHEET

Product Name

Platinum Gloss Art Fibre 300gsm

Product Description

Platinum Gloss Art Fibre is 100% Alpha-cellulose paper with a distinctive texture – guarantees archival standards. Its premium high-gloss inkjet coating meets the highest industry standards regarding density, colour gamut, colour graduation and image sharpness. Compatible with pigment and dye inkjet systems.

Technical Information

Thickness	440µm
Weight (gsm)	300gsm
Coating Type	Unglazed gloss
OBA	Yes
Whiteness (CIE)	104
Brightness (TAPPI)	-
pH	8.2
Opacity	99
Recyclable	Yes

Features

- Smooth glossy surface
- Fibre based photo quality
- Archival – acid and lignin free
- Pigment and dye ink compatible
- Excellent colour gamut for colour photography
- Exceptional D-max up to 2.7

Media Availability

ROLLS	12"	13"	16"	17"	24"	36"	44"	50"	54"	60"	64"
	-	-	-	-	•	•	•	-	-	-	-
SHEETS	6x4	5x7	8x10	A4	A3	A3+	A2	Panoramic			
	-	-	-	•	•	•	•	-			

Suggested Applications

- Fine art and photographic open and limited edition prints
- Fine art and photographic reproduction and restoration
- Portfolios
- Albums
- Cards and postcards

Paper Handling

- Fine Art papers are fragile and need to be handled with care. Try not to touch the surface of the paper.
- Glossy papers will mark more easily with grease from your fingertips.
- Leave papers open to the air to fully dry for a few hours after printing, (24 hours are recommended) and avoid stacking on top of each other straight away.
- A giclée varnish or spray will help protect your print further from damage, effects of UV light and environmental attack.

Storage and Conditions of Use

- The storage of all papers should take place in a recommended climate of 15-25°C, relative humidity of 40 - 60% and out of direct sunlight.
- Do not exceed temperatures of 82°C (180°F) when dry mounting.
- Return unused paper to the original box and store flat. If storing the paper outside the original box, only use archival packaging.